

MACE 61058: Plasticity – Lab report: tensile

Lecturers: Dr. Henry Tan; Operator: Mr David Mortimer and Mr Peter Hassall

Deadline: Friday 24/4/2009, 4pm

Submission: George Begg Coursework Box: Plasticity (Lab report - tensile)

Objective: Use uniaxial tensile test to study the mechanical behaviours of steel, aluminum and copper.

Specimen data

The specimens are 12.5mm in diameter. The initial gauge length is $l_0 = 375\text{mm}$.

Test data

The tensile test data can be downloaded from Blackboard: [Your Study > Plasticity - theory > Lab report](#)
tensile-aluminium.txt
tensile-copper.txt
tensile-steel.txt

For each file, the first column is the data acquisition step number, **the second column is the displacement in unit mm (millimetre), the third column is the load in unit kN (kilonewton).**

Report requirement:

You may need software, such as Excel, for drawing the curves.

- (1) For copper, draw the engineering stress – strain curve and the true stress – strain curve in one figure, compare the difference between the two curves. [1 mark]
- (2) Draw the true stress – strain curves for aluminium, copper and steel in one figure, compare the stress-strain behaviours of three materials. [2 mark]
- (3) Using the elastic – linear hardening model, as shown in Figure 1, to approximate the true stress-strain curves.




Figure 1. Stress (true) - strain (true) curve from a uniaxial test.

Determine the values of yield stress (σ_y), Young's modulus (E) and tangential modulus after yielding (E_t) for aluminium, copper and steel based on the experimental data. [4 mark]

Marking:

This report weights 7% of the overall final.